

FCL30

Free Chlorine Tester



Precision easy operation: all functions operated in one hand.

Large LCD with backlight, Multi-line display for easy reading, Auto-Power Off saves battery after 5 mins non-use.

1*1.5V AAA long battery life

Easy maintenance, simple to change battery and electrode

Floats on water, IP67 rated

Field throw measurement (Auto Lock Function)



CLEAN FCL30 Free Chlorine Tester

- Use tri-electroded method measuring: faster and accurate, matching up to DPD results.
- 2 points calibrate.

Range	0 - 10.00 mg/L
Resolution	0.01 mg/L
Accuracy	±5% F.S.
Temp. Range	0 - 100.0 °C / 32 - 212 °F
Working Temperature	0 - 60.0 °C / 32 - 140 °F
Calibration Point	2 points
LCD	20* 30 mm multi-line crystal display
Lock	Auto / Manual
Electrode	CS5930
Auto backlight off	1 minutes
Auto power off	5 minutes without key be pressed
Power	1x1.5V AAA battery
Dimensions	(H×W×D) 185×40×48 mm
Weight	95g
Protection	IP67

Revolutionary way to instantly get free chlorine value by using tri-electroded method measuring: faster and accurate, matching up to DPD results, without any reagent consuming. FCL30 in your pocket is a smart partner to measure free chlorine with you.



www.cleaninst.com
Water Analysis Solutions